



Basic performance parameter of reduction motor

客户名称	Model of Motor	G6BLD300-24-18S	
	Rated Voltage	DC24V	Ambient temperature -10℃~40℃
	Rated Power	300W	Humidity Relative humidity below 90%
	Rated Current	16.67A	
	Rated Speed	1800±5%rpm	yellow line(CMU): Brushless motor winding U-phase white line(CMV): Brushless motor winding V-phase blue line(CMW): Brushless motor winding W-phase fine red line(CVCC): Hall signal line power supply fine yellow line(CHU): Hall signal U-phase input fine white line(CHV): Hall signal V-phase input fine blue line(CHW): Hall signal W-phase input fine black line(CGNDI): Hall signal ground
	Rated Torque	1.59N.m	
借(通)用件登记 旧底图总号	N0-load Cur	<5A	
底图总号	non load Speed	2100±5%rpm	
	Duty cycle	S1	
签字	Insulation resistance	>50MΩ	
	Hall sensing position configuration	Three-phase 120-degree electric foot configuration 6.25V power supply	
日期	Electrical strength	650V/S	
	Insulation grade	E	
	Protection Grade	IP44	

请确认		
客户签名	日期	
产品编码		

				OUTLINE DRAWING				
标记	次数	更改文件号	签字	日期	图样标记	重量	比例	DC Blushless MOTOR
设计			标准化		S		1:1	G6BLD300-24-18S
校对			审定					
审核								
工艺			日期		共 1 页	第 1 页		