



Basic performance parameter of reduction motor

客户名称	Model of Motor	G6BLD600-48-30S	
	Rated Voltage	DC48V	Ambient temperature -10℃~40℃
	Rated Power	600W	Humidity Relative humidity below 90%
	Rated Current	15.625A	
	Rated Speed	3000±5%rpm	
借(通)用件登记 旧底图总号	Rated Torque	1.91N.m	yellow line(CMU): Brushless motor winding U-phase white line(CMV): Brushless motor winding V-phase blue line(CMW): Brushless motor winding W-phase fine red line(CVCC): Hall signal line power supply fine yellow line(CHU): Hall signal U-phase input fine white line(CHV): Hall signal V-phase input fine blue line(CHW): Hall signal W-phase input fine black line(CGND): Hall signal ground
	NO-load Cur	<4.69A	
底图总号	non load Speed	3300±5%rpm	
	Duty cycle	S1	
签字	Insulation resistance	>50MΩ	
	Hall sensing position configuration	Three-phase 120-degree electric foot configuration 6.25V power supply	
日期	Electrical strength	650V/S	
	Insulation grade	E	
	Protection Grade	IP44	

请确认

客户签名	日期
产品编码	

OUTLINE DRAWING				DC Blushless MOTOR	
标记	处数	更改文件号	签字	日期	
设计			标准化		
校对			审定		
审核					
工艺			日期		
图样标记			重量	比例	
S				1:1	
共 1 页			第 1 页		G6BLD600-48-30S